

Specifications

Model			1000S	1200S	1400S	1600S	1800S	2000S	2200S	2400S
Operating height			42' 6"	47' 6"	50' 0"	57' 6"	61' 3"	66' 3"	71' 3"	75' 0"
Tower diameter			11' 8"	11' 8"	11' 8"	11' 8"	11' 8"	11' 8"	11' 8"	11' 8"
Centrifugal Blower horsepower			2@ 30	2@ 30	2@ 30	2@ 40	2@ 40	2@ 50	2@ 50	2@ 50
Grain Column thickness (VARIABLE)			10"-12"	10"-12"	10"-12"	10"-12"	10"-12"	10"-12"	10"-12"	10"-12"
Typical burner Use at 60F. (Suction Cool) BTU's in millions			7.30M	7.59M	8.19M	9.35M	10.02M	10.66M	11.10M	11.50M
Metering unit standard H.P.			5	5	5	5	5	5	5	5
Capacities in Dry and Cool Bushels Per Hour										
Corn	20 to 15%	DRY/COOL	1000	1200	1400	1500	1800	2000	2200	2400
Corn	25 to 15%	DRY/COOL	670	780	900	1000	1180	1250	1475	1610
Corn	23 to 18%	ALL HEAT	1300	1560	1820	2080	2340	2600	2860	3120
Corn	28 to 18%	ALL HEAT	850	1020	1200	1360	1530	1700	1870	2040
Wheat	18 to 13%	DRY/COOL	1200	1440	1680	1920	2160	2400	2640	2880
Soy-beans	18 to 13%	DRY/COOL	670	800	940	1070	1205	1340	1475	1610
Rice 3Pt.	One Pass	ALL HEAT	1500	1750	1960	2400	2520	2800	3300	3600
Milo	19 to 14%	DRY/COOL	900	1080	1260	1440	1620	1800	1980	2160